


Industrial

Diesel Engine 6R 1000

for C&I Applications

with EPA Tier 4 and EU Stage IV Certification



Dimensions and Masses

Engine	Dimensions (LxWxH) mm (in)	Mass, dry kg (lbs)
6R 1000 C	1099x1106x1029 (43.3x43.3x40.5)	705 (1555)

All dimensions are approximate, for complete information refer to the installation drawing.

Engine Model		
Bore/stroke	mm (in)	110/135 (4.3/5.3)
Cylinder configuration		6 inline
Displacement, total	l (cu in)	7.7 (470)
Fuel specification		DIN EN 590, ASTM D975 (DF1, DF2)

Engine Type	Rated Power			Peak Torque			Fuel Consumption at rated power	Fuel Consumption at peak torque
	Model	kW	bhp	rpm	Nm	lb-ft	rpm	g/kWh
6R 1000 C20	180	241	2200	1000	738	1200-1600	212	196
6R 1000 C30	210	281	2200	1150	848	1200-1600	212	196
6R 1000 C40	230	308	2200	1250	922	1200-1600	212	196
6R 1000 C50	260	348	2200	1400	1033	1200-1600	212	196

Ratings acc. to ECE R 120

1) Emissions: EPA: US Nonroad Regulation 40 CFR 89 Tier 4
EU: EU Directive 97/68/EC stage IV



Power. Passion. Partnership.

Standard Equipment

24 Volt starter

28 Volt alternator, 100 A

Common rail injection system

Electronic engine management

Electronic interface module

Turbo charging air to air cooling

High pressure EGR system

One-box aftertreatment system with SCR and DPF* incl. muffler

Close crankcase ventilation

SAE 1 flywheel housing

* Development without DPF in progress

Reference conditions:

> Intake temperature: 25°C (77°F)

> Charge air temperature: 40°C

> Altitude: 200 m (656 ft)

> Air intake restriction: 25 mbar

Subject to change without notice. Customization possible. Engines illustrated in this document may feature options not fitted as standard to standard engine.

Optional Equipment

Exhaust brake system

SAE 2 flywheel housing

Aux REPTO

Air compressor

AC compressor

Flex engine mounts

Elevated fan drive

Cooling fan